# NSN 2910-01-167-2932

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-01-167-2932

## Mounting Type:

Bracket w/drilled hole head side

#### Mounting Hole Diameter:

10.30 millimeters

# Mounting Hole Quantity:

4

### Body Outside Diameter:

120.8 millimeters

#### **Body Height:**

341.0 millimeters

#### **Distance Between Mounting Hole Centers:**

124.0 millimeters

#### End Application:

Nsn 2320-01-303-2277 pls (palletized loading system)

#### **Design Type:**

Reusable

# Bracket Quantity:

1

## Filtering Element Quantity:

1

#### Maximum Operating Pressure:

31.0 pounds per square inch

# Criticality Code Justification:

Feat

# First Intake Connection Type:

Threaded internal tube head

# First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

# First Intake Thread Series Designator:

Un

# First Intake Thread Size:

1.312 inches

# First Intake Thready Qty Per Inch (tpi):

12

#### First Intake Thread Class:

2b

### First Intake Thread Direction:

**Right-hand** 

# Filtering System For Which Designed:

Full flow

#### **Special Features:**

Weapon system essential

# NSN 2910-01-167-2932

Fluid Filter - Page 2 of 2

Material:

Steel body

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

Quick-disconnect shell

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A24000

