## NSN 2910-01-361-8229

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-01-361-8229

Mounting Type:
Bracket w/drilled hole head side
Mounting Hole Diameter:
5.16 millimeters
Mounting Hole Quantity:
2
Body Outside Diameter:
111.3 millimeters
Body Height:
210.6 millimeters
Filtration Rating In Microns:
30.0
Distance Between Mounting Hole Centers:
67.46 millimeters
End Application:
Fmtv
Design Type:
Reusable
Features Provided:
Drain plug
Bracket Quantity:
1
Filtering Element Quantity:
1
Maximum Operating Pressure:
0.47 pounds per square inch
Filtering Media Design:
Pleated single filtering media response
First Intake Connection Type:
Threaded internal tube head side
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Unf
First Intake Thread Size:
0.562 inches
First Intake Thread Class:
3b
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:

## NSN 2910-01-361-8229

Fluid Filter - Page 2 of 2



Special	Features:
---------	-----------

Bowl heater 24v-200w, snap-on at 45.0deg f, off at 85.0deg f; media diesel fuel; bowl clear plastic for visual inspection; low pressure, 28gph; drain has hose connect, barb for 5/16in. Id

Material:

Plastic container/cartridge

Media For Which Designed:

Fuel/oil, hydrocarbon

**Style Designator:** 

Quick-disconnect shell

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A24000