

View Online at <https://aerobasegroup.com/nsn/2910-01-385-1773>

**Thread Direction:**

Right-hand

**Mounting Type:**

Unthreaded hole head

**Mounting Hole Diameter:**

Between 0.278 inches and 0.287 inches

**Mounting Hole Quantity:**

2

**Body Outside Diameter:**

2.776 inches

**Body Height:**

6.380 inches

**Filtration Rating In Microns:**

10.0

**Drop Pressure:**

8.0 pounds per square inch

**Differential Pressure:**

9.0 pounds per square inch

**Distance Between Mounting Hole Centers:**

2.960 inches

**Design Type:**

Nonreusable

**Temperature Rating:**

Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit

**Filtering Element Quantity:**

1

**Maximum Operating Pressure:**

50.0 pounds per square inch

**First Intake Connection Type:**

Threaded internal tube head

**First Discharge Connection Relationship To Intake Connection:**

Not identical

**First Discharge Connection Type:**

Threaded internal tube head

**First Intake Thread Series Designator:**

Unjf

**First Discharge Thread Series Designator:**

Unjf

**First Intake Thread Size:**

0.5625 inches

**First Discharge Thread Size:**

0.4375 inches

**First Intake Thread Class:**

3b

**First Discharge Thread Class:**

3b

**First Intake Thread Direction:**

Left-hand

**First Discharge Thread Direction:**

Left-hand

**Filtering System For Which Designed:**

Full flow

**Special Features:**

Proof psi 100.0; burst psi 150.0; pacer dawn-apu

**Material:**

Nickel alloy body

**Media For Which Designed:**

Fuel/oil, hydrocarbon

**Style Designator:**

High pressure threaded body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000