

View Online at <https://aerobasegroup.com/nsn/2910-01-385-1773>

Thread Direction:

Right-hand

Mounting Type:

Unthreaded hole head

Mounting Hole Diameter:

Between 0.278 inches and 0.287 inches

Mounting Hole Quantity:

2

Body Outside Diameter:

2.776 inches

Body Height:

6.380 inches

Filtration Rating In Microns:

10.0

Drop Pressure:

8.0 pounds per square inch

Differential Pressure:

9.0 pounds per square inch

Distance Between Mounting Hole Centers:

2.960 inches

Design Type:

Nonreusable

Temperature Rating:

Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit

Filtering Element Quantity:

1

Maximum Operating Pressure:

50.0 pounds per square inch

First Intake Connection Type:

Threaded internal tube head

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Threaded internal tube head

First Intake Thread Series Designator:

Unjf

First Discharge Thread Series Designator:

Unjf

First Intake Thread Size:

0.5625 inches

First Discharge Thread Size:

0.4375 inches

First Intake Thread Class:

3b

First Discharge Thread Class:

3b

First Intake Thread Direction:

Left-hand

First Discharge Thread Direction:

Left-hand

Filtering System For Which Designed:

Full flow

Special Features:

Proof psi 100.0; burst psi 150.0; pacer dawn-apu

Material:

Nickel alloy body

Media For Which Designed:

Fuel/oil, hydrocarbon

Style Designator:

High pressure threaded body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A24000