## NSN 2910-01-419-6286

Fluid Filter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/2910-01-419-6286                |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|
| Mounting Type:   |  |  |  |  |  |  |  |
| Inlet connection end and outlet connection end                               |  |  |  |  |  |  |  |
| Body Length:   |  |  |  |  |  |  |  |
| 3.250 inches   |  |  |  |  |  |  |  |
| Filtration Rating In Microns:  |  |  |  |  |  |  |  |
| 40.0   |  |  |  |  |  |  |  |
| Drop Pressure:   |  |  |  |  |  |  |  |
| 1500.0 pounds per square inch  |  |  |  |  |  |  |  |
| End Application:   |  |  |  |  |  |  |  |
| 2350-01-248-7619; weapon system e/i fighting vehicle systems, bradley (bfvs) |  |  |  |  |  |  |  |
| Design Type:   |  |  |  |  |  |  |  |
| Reusable   |  |  |  |  |  |  |  |
| Tempurature Rating:  |  |  |  |  |  |  |  |
| Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit                |  |  |  |  |  |  |  |
| Filtering Element Quantity:  |  |  |  |  |  |  |  |
| 1  |  |  |  |  |  |  |  |
| Maximum Operating Pressure:  |  |  |  |  |  |  |  |
| 3000.0 pounds per square inch  |  |  |  |  |  |  |  |
| Filtering Media Design:  |  |  |  |  |  |  |  |
| Sintered single filtering media response                                     |  |  |  |  |  |  |  |
| First Intake Connection Type:  |  |  |  |  |  |  |  |
| Threaded internal tube end   |  |  |  |  |  |  |  |
| First Discharge Connection Relationship To Intake Connection:                |  |  |  |  |  |  |  |
| Identical to first intake connection   |  |  |  |  |  |  |  |
| First Intake Thread Series Designator:                                       |  |  |  |  |  |  |  |
| Unf  |  |  |  |  |  |  |  |
| First Intake Thread Size:  |  |  |  |  |  |  |  |
| 0.562 inches   |  |  |  |  |  |  |  |
| First Intake Thread Class:   |  |  |  |  |  |  |  |
| 2b   |  |  |  |  |  |  |  |
| First Intake Thread Direction:   |  |  |  |  |  |  |  |
| Right-hand   |  |  |  |  |  |  |  |
| Filtering System For Which Designed:   |  |  |  |  |  |  |  |
| Full flow  |  |  |  |  |  |  |  |
| Material:  |  |  |  |  |  |  |  |
| Copper alloy filtering medium  |  |  |  |  |  |  |  |
| Media For Which Designed:  |  |  |  |  |  |  |  |
| Fuel/oil, hydrocarbon  |  |  |  |  |  |  |  |
| Style Designator:  |  |  |  |  |  |  |  |
| Inline (hydraulic)   |  |  |  |  |  |  |  |
| Shelf Life:  |  |  |  |  |  |  |  |

N/a

## NSN 2910-01-419-6286

Fluid Filter - Page 2 of 2



|  |  |  | ıre: |
|--|--|--|------|
|  |  |  |      |

--

Demilitarization:

No

Fiig:

A24000