NSN 2910-01-470-4088

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-01-470-4088

Thread Direction:
Right-hand
Mounting Type:
Bracket w/drilled hole line
Mounting Hole Diameter:
0.325 inches
Mounting Hole Quantity:
2
Body Outside Diameter:
2.300 inches
Body Height:
6.500 inches
Filtration Rating In Microns:
30.0
Drop Pressure:
0.17 pounds per square inch
Differential Pressure:
Not rated
Distance Between Mounting Hole Centers:
0.500 inches
End Application:
Boat bridge erection
Design Type:
Nonreusable
Features Provided:
Air bleed valve
Bracket Quantity:
1
Filtering Element Quantity:
1
Maximum Operating Pressure:
60.0 pounds per square inch
Filtering Media Design:
Any acceptable all filtering media responses
First Intake Connection Type:
Threaded internal pipe head side
Second Intake Connection Relationship To First Intake Connection:
Identical
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Npt

NSN 2910-01-470-4088 Fluid Filter - Page 2 of 2



First Intake Thread Size:
0.3750 inches
Product Name:
Fuel filter/water separator
First Intake Thread Direction:
Right-hand
Filtering System For Which Designed:
Full flow
Special Features:
Pump, in-head priming
Material:
Aluminum alloy frame
Media For Which Designed:
Fuel/oil, hydrocarbon
Style Designator:
Threaded shell (mason jar)
Supplementary Features:
Contamination bowl, see through
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A24000