## NSN 2910-01-507-1056

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-01-507-1056

Thread Direction:
Right-hand
Mounting Type:
Unthreaded hole top side
Mounting Hole Diameter:
0.375 inches
Mounting Hole Quantity:
2
Body Outside Diameter:
4.000 inches
Body Height:
9.375 inches
Filtration Rating In Microns:
10.0
Drop Pressure:
0.61 pounds per square inch
End Application:
7 meter rigid hull inflatable boat.
Design Type:
Reusable
Tempurature Rating:
-40.0 degrees fahrenheit and 255.0 degrees fahrenheit
Filtering Element Quantity:
1
Maximum Operating Pressure:
7.0 pounds per square inch
First Intake Connection Type:
Threaded internal pipe head side
Second Intake Connection Relationship To First Intake Connection:
Identical
First Discharge Connection Relationship To Intake Connection:
Identical to first intake connection
First Intake Thread Series Designator:
Nptf
First Intake Thread Size:
0.250 inches
First Intake Thready Qty Per Inch (tpi):
18
Product Name:
Gasoline/fuel filter/water seperator
First Intake Thread Direction:

Right-hand

## NSN 2910-01-507-1056

Fluid Filter - Page 2 of 2



<b>Filtering</b>	<b>System</b>	For Wh	nich De	sianed:

Full flow

## **Special Features:**

Versatile three-port aluminum head anodized and powder painted. Directs incoming fuel flow to the spin-on replaceable element. Inlet both sides out in front. 10 micron media. Spin-off bowl/element. See-thru bowl assembly at bottom. Self-venting drain valve. Replacement filter p/n s3227, nsn 2910-01-507-1442.

## Media For Which Designed:

Fuel/oil, hydrocarbon

**Style Designator:** 

Threaded shell (mason jar)

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A24000