# NSN 2910-01-507-1056

Fluid Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2910-01-507-1056

Thread Direction:

Right-hand

Mounting Type:

Unthreaded hole top side

Mounting Hole Diameter:

0.375 inches

Mounting Hole Quantity:

2

Body Outside Diameter:

4.000 inches

**Body Height:** 

9.375 inches

Filtration Rating In Microns:

10.0

Drop Pressure:

0.61 pounds per square inch

### **End Application:**

7 meter rigid hull inflatable boat.

Design Type:

Reusable

**Tempurature Rating:** 

-40.0 degrees fahrenheit and 255.0 degrees fahrenheit

## Filtering Element Quantity:

1

### Maximum Operating Pressure:

7.0 pounds per square inch

### First Intake Connection Type:

Threaded internal pipe head side

# Second Intake Connection Relationship To First Intake Connection:

Identical

# First Discharge Connection Relationship To Intake Connection:

Identical to first intake connection

# First Intake Thread Series Designator:

Nptf

# First Intake Thread Size:

0.250 inches

# First Intake Thready Qty Per Inch (tpi):

18

### **Product Name:**

Gasoline/fuel filter/water seperator

## First Intake Thread Direction:

**Right-hand** 

# NSN 2910-01-507-1056

Fluid Filter - Page 2 of 2



# Filtering System For Which Designed:

Full flow

# **Special Features:**

Versatile three-port aluminum head anodized and powder painted. Directs incoming fuel flow to the spin-on replaceable element. Inlet both sides out in front. 10 micron media. Spin-off bowl/element. See-thru bowl assembly at bottom. Self-venting drain valve. Replacement filter p/n s3227, nsn 2910-01-507-1442.

## Media For Which Designed:

Fuel/oil, hydrocarbon

## Style Designator:

Threaded shell (mason jar)

## Shelf Life:

N/a

# Unit Of Measure:

---

### Demilitarization:

No

### Fiig:

A24000