

View Online at <https://aerobasegroup.com/nsn/2910-01-528-6664>

Terminal Type:

Screw

Current Type:

Ac and dc

Body Length:

9.820 inches

Body Width:

4.570 inches

Body Height:

9.820 inches

End Application:

Engine diesel 6 cyl 474bhp 1800rpm

Shaft Rotation Direction:

Clockwise

Duty Cycle:

Adjustable

Manual Override:

Included

Product Name:

M9216 series electric spring return actuator

Voltage In Volts:

24.0

Special Features:

Power requirement: 20 to 30 vac at 50/60 hz or 24 vdc plus/minus 10 percent, 10 va supply , class 2. Input signal: 24 vac at 50/60 hz or 24 vdc, 420 ma max. Spring return: factory setting-ccw direction is selectable with the coupler. Mechanical output running torque: 140 lbs/in (16 n/m) for one unit. Rotation time: 70 to 130 seconds for 0 to 140 lb/in (0 to 16 n/m); 90 seconds at 50 percent rated load. Cycles: 65,000 full stroke cycles. Electrical connection: screw terminals for 22 to 14 awg (insert a maximum of two 18, 20, or 22 awg per terminal). Temperature ranges: -4 to 122 degrees fahrenheit (storage: -40 to 186 degrees fahrenheit). Shipping weight: 6.4 lbs.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A30500