

View Online at <https://aerobasegroup.com/nsn/2915-00-049-3673>

**General Description:**

Link, cres, chrome plated, 60 min, 75 maximum rockwell b scale hardness, each end 0.2187 in. Radius, 0.0568 in. Min, 0.0638 in. Maximum thk, two holes 1.641 in. Effective lg, 0.252 in. Min, 0.254 in. Maximum dia, clip, spring steel, nickel plated, 0.016 in. Thk, one hole 0.201 in. Min, 0.202 in. Maximum dia, stud, no. 5, carpenters steel, 0.297 in. O/a lg, 0.313 in. Diameter head, lever, cres, sae1010, chrome plated, one hole 0.201 in. Min, 0.202 in. Maximum dia, onethd hole no. 10-32 anf thd, screw, 0.373 in. Min, 0.383 in. Maximum o/a lg, 0.250 in. Min, 0.255 in. Maximum diameter head, 0.094 in. Head thk, shank end, no. 10-32 nf-2a thd, 0.232 in. Min, 0.242 in. Maximum thd lg, chamfered 0.047in. 45 deg, 20 teeth equally spaced on head, drive head, screwdriver 9002a2

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No