

View Online at <https://aerobasegroup.com/nsn/2915-00-156-8831>

**General Description:**

Plunger rod, steel sae 1112, brass plated, 0.672 in. H, 0.156 in. Min, 0.158 in. Maximum od, stem, steel, copper plated, 1.500 in. H, one end 0.124 in. Min, 0.126 in. Maximum od, other end 0.141 in. Min, 0.143 in. Maximum od, flange 0.109 in. Thk, 0.219 in. Od, washer, steel, brass plated, 70 min, 85 maxrockwell b scale hardness, 0.720 in. Min, 0.724 in. Maximum od, 0.047 in. Thk, center punch 0.127 in. Min, 0.129 in. Maximum dia, plunger, 0.750 in. Od, pump, calfskin leather, 0.240 in. Min, 0.310 in. Maximum od, 0.178 in. Min, 0.248 in. Max id, 0.031 in. Thk, 0.219 in. Min, 0.250 in. Maximum deep, center hole on top 0.129 in. Min, 0.134 in. Maximum dia, spring, music wire, copper plated, 2.125 in. Free lg, 10 coils, ends closed and ground flat, spring seat, steelbrass plated, 40 min, 50 maximum rockwell b scale hardness, 0.500 in. Dia, 0.088 in. H

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No