

View Online at <https://aerobasegroup.com/nsn/2915-00-640-0231>

**General Description:**

Rdesigned for partially submerged operation; non pos displacement type pump; pump data, 1 impeller, single stage, pump capacity rating, 3600phr, max rated capacity at min psi, 20psi, min pressure at maximum rated capacity; vertical design; vertical design dim data, 12.046 in. H o/a parallel to shaft axis, 8.109 in. H from top of mtg flange to farthest end, 4.875 in. W o/a perpendicular to shaft axis, 7.342 in. Lg o/a perpendicular to shaft axis; ccw rotation; inlet opening w/strainer; outlet connection data, 1 tube connection; no govt specification or std; external discharge; thd connection, 1-5-16 in. 12 un 3 thd designation, external thd, rh thd, stationary design, not flanged connection; mtg data, fixed flange mtg, not govt specification or standard mtg flange, 12 bolt holes 0.281 in. Diameter bolt holes, irregularly spaced around oval flange; elec motor driven, 1-3 hp rating, elec operating power data, dc, 27v, 17.5 amp rating, 8700 rpm, not provided w/controller; elec connection data, 3, wire lead type terminal, shielded, 1 ft lg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A23900