

View Online at <https://aerobasegroup.com/nsn/2915-00-872-5855>

General Description:

Aluminum alloy, qq-a-225/6 comp 2024 temper t4, w/carbon insert, 0.341 in. Min, 0.345 in. Maximum o/a w, 0.870 in. Min, 0.880 in. Maximum od flange, 0.145 in. Min, 0.155 in. Maximum lg flange, 0.505 in. Nom od body, 2 slots on flange od located 180 degrees apart, 0.180 in. Nom w slots, 0.145 in. Min, 0.155 in. Maximum lg slots, 0.095 in. Min, 0.115 in. Maximum depth slots, 30 degrees by 0.030 in. Nom lg chamfer on body od, stepped id, 0.139 in. Min, 0.141 in. Maximum id insert 1st step 1st end, 0.130 in. Nom lg insert 1st step 1st end, 0.183 in. Min, 0.187 in. Maximum id 2nd step 1st end, 0.110 in. Min, 0.120 in. Maximum lg 2nd step 1st end, 0.296 in. Min, 0.300 in. Maximum id 3rd step 1st end, 0.090 in. Min, 0.095 in. Maximum lg 3rd step 1st end, 0.183 in. Min, 0.185 in. Maximum id 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli