

View Online at <https://aerobasegroup.com/nsn/2915-00-926-8336>

**Overall Length:**

Between 3.360 inches and 3.480 inches

**Power Cable Length:**

Between 60.000 inches and 66.000 inches

**Dc Voltage Rating:**

28.0 volts

**Overall Diameter:**

1.380 inches

**Electrical Connection Type:**

Cable

**Internal Battery Accommodation:**

Not included

**Current Rating At Maximum Rated Voltage:**

500.0 milliamperes load

**Voltage Rating At Maximum Rated Current:**

28.0 volts

**Float Quantity:**

1

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Thread

**Mounting Position:**

Vertical

**Maximum Current Rating:**

500.0 milliamperes load

**Contact Arrangement:**

Single throw, normally closed

**Relay:**

Not included

**Liquid Type For Which Designed:**

Aircraft fuel

**Aircraft Fuel For Which Designed:**

Specific

**Aircraft Fuel Grade Specificationification:**

Mil-g-5572, mil-t-5624

**Aircraft Fuel Grade:**

80/87, 100/130, 115/145, jp-4, jp-5

**Aircraft Fuel Grade Specificationific Gravity Rating:**

0.782 at 15.6/15.6 degrees c, maximum sp gr, 0.845 at 15.6/15.6 degrees c, maximum sp gr

**Float Effective Travel:**

Between 1.250 inches and 1.500 inches

**Mounting Dimensions:**

Mtd by bulkhead fitting per ms33657s6 thd size 9-16-18 unf-3a

**Tank Insertion Length:**

Between 2.240 inches and 2.360 inches

**Fsc Application Data:**

Aircraft engine float switch

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T109-d

**Mil-std (military Standard):**

Mil-g-5572 spec.