NSN 2915-00-940-9940

Afterburner Igniter Valve Lever - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2915-00-940-9940

End Application:

Tf30-p-1 aircraft fuel control

General Description:

Material stainless steel, rockwell-c 35 to 40 hardness, o/a dim. Approx 2.203 in. Min to 2.258 in. Maximum Ig by 0.970 in. Min to 0.986 in. Maximum w, 2 holes, 0.093 in. Min to 0.095 in. Maximum on either side of middle section, large end dim. 0.490 in. Min to 0.510 in. Maximum diameter w/6 slots, approx 0.190 in. Min to 0.210 in. Maximum Ig by 0.073 in. Min to 0.088 in. Maximum w, equally spaced, fitting approx 0.047 in. Min to 0.078 in. Maximum radius by 0.080 in. Min to 0.100 in. Maximum thk, small end dim. 0.270 in. Min to 0.290 in. Maximum w w/slot approx 0.360 in. Min to 0.400 in. Maximum Ig by 0.103 in. Min to 0.104 in. Maximum w

| $\overline{}$ | | | • | |
|---------------|----|----|-------|----|
| • | he | IΤ | ITA | Δ. |
| | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli