NSN 2915-00-974-0185

Lever Pull Rod - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2915-00-974-0185

General Description:

Aluminum alloy, qq-a-225/8, rockwell 30t scale 49.5 min hardness, 3.721 in. Nom o/a Ig, stepped od, 0.120 in. Min, 0.130 in. Maximum od 1st step 1st end, 0.060 in. Nom Ig 1st step 1st end, ext thd 2nd step 1st end, no. 10-0.190 in.-32 unf cl 2a thd, 0.530 in. Nom Ig 2nd step 1st end, 0.184 in. Min, 0.187 in. Maximum od 3rd step 1st end, 0.881 in. Nom Ig 3rd step 1st end, 1 hole 0.046 in. Nom diameter through od 2nd step ist end, 0.4373 in. Min, 0.4375 in. Maximum od 1st step 2nd end, 2.310 in. Nom Ig 1st step 2nd end, 0.285 in. Nom w across flats, 0.140 in. Nom distance from 2nd end to flats, 1 hole 0.125 in. Min, 0.126 in. Maximum diameter through flatted section of od 1st step 2nd end Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli