

View Online at <https://aerobasegroup.com/nsn/2915-00-992-5761>

End Application:

T53M-FR-291-5012

General Description:

Aluminum alloy, ams4120, anodized finish, ams2470, 63 microinch aa surface finish grooves, 125 microinch aa surface finish od, 250 microinch aa finish remaining surfaces, 2.455 in. Min, 2.465 in. Maximum o/a lg, stepped od, 0.306 in. Min, 0.308 in. Maximum od 1st step 1st end, 0.160 in. Min, 0.166 in. Maximum lg 1st step 1st end, 0.250 in. Nom diameter 2nd step 1st end, 1.643 in. Min, 1.669 in. Maximum lg 2nd step 1st end, 0.306 in. Min, 0.308 in. Maximum diameter 1st step 2nd end, 0.609 in. Min, 0.619 in. Maximum lg 1st step 2nd end, 1 ext groove maximum lg 1st step 2nd end, 1 ext groove 1st step 1st end, 0.099 in. Min, 0.109in. Maximum w by 0.207 in. Min, 0.211in. Maximum diameter groove, 0.048 in. Min, 0.064 in. Maximum distance from 1st end to groove, 2 ext grooves 1st step 2nd end, 0.099 in. Min, 0.109 in. Maximum w by 0.207 in. Min, 0.211 in. Maximum diameter grooves, 0.071 in. Min, 0.081 in. Maximum distance from 2nd end to 1st groove, 0.480 in. Nom distance from 2nd end to 2nd groove, chamfered od both ends, 0.020 in. Min, 0.030 in. Maximum lg by 45 degrees chamfer 1st end, 0.040 in.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli