

View Online at <https://aerobasegroup.com/nsn/2915-01-018-2491>

**General Description:**

Stainless steel, ams5360, rockwell c scale 53 min, 60 maximum hardness, 0.764 in. Min, 0.768 in. Maximum o/a lg, stepped od, 0.450 in. Nom od 1st step 1st end, 0.093 in. Min, 0.103 in. Maximum lg 1st step 1st end, 0.623 in. Min, 0.628 in. Maximum od 2nd step 1st end, 0.202 in. Min, 0.214 in. Maximum lg 2nd step 1st end, 0.5899 in. Min, 0.5904 in. Maximum od 1st step 2nd end, 0.457 in. Min, 0.463 in. Maximum lg 1st step 2nd end, 1 groove on od 1st step 2nd end, 0.555 in. Min, 0.565 in. Maximum dp groove, 0.039 in. Min, 0.042 in. Maximum w groove, 0.059 in. Min, 0.071 in. Maximum distance from 2nd end to groove, 45 degrees by 0.030 in. Nom lg chamfer on od 2nd end, 1st end, slotted face, 0.126 in. Min, 0.128 in. Maximum w slot, 0.135 in. Min, 0.155 in. Maximum dp slot, 0.450 in. Nom lg slot, 2nd end internally splined, 8 teeth, 30 degrees pressure angle, 0.3333 in. Nom pitch dia, 0.557 in. Min, 0.570 in. Maximum lg splines

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli