## NSN 2915-01-196-8281

Linear Electro-mechanical Actuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/2915-01-196-8281



**Terminal Type:** Connector **Tempurature Rating:** 0.0 degrees celsius and 50.0 degrees celsius **Current Type:** Ac **Body Length:** Between 10.080 inches and 10.320 inches **Body Width:** Between 8.295 inches and 8.555 inches **Body Height:** Between 6.790 inches and 7.150 inches **Environmental Protection:** Watertight **Maximum Operating Altitude Rating:** 50.0 feet **Duty Cycle:** Intermittent **Current Rating In Amps:** 2.8 Stroke Length: Between 2.000 inches and 3.125 inches **Limit Switch Control:** Included **Thermal Protector Reset Method:** Automatic **Err Default:** Err default **Manual Override:** Included **Tension Load Rating:** 300.0 pounds operating **Compression Load Rating:** 300.0 pounds operating **Rated Stroke Velocity:** 8.000 inches per minute and 14.000 inches per minute **Intermittent Operation Duty Cycle:** 15.0 seconds on and 1.0 seconds off **Mounting Facility:** Threaded mounting holes Voltage In Volts: 115.0

## NSN 2915-01-196-8281

Linear Electro-mechanical Actuator - Page 2 of 2



Single

Frequency In Hertz:

60.0

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A30500