

View Online at <https://aerobasegroup.com/nsn/2920-00-008-9912>

**Thread Direction:**

Right-hand

**Thread Length:**

0.390 inches

**Pilot Diameter:**

2.000 inches

**Furnished Items:**

Cooling fan and lockwasher and nut and woodruff key

**Second Step Diameter:**

0.627 inches

**Keyway Width:**

0.125 inches

**Unthreaded Portion Length:**

0.625 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Flange mtd w/two mtg holes, top hole threaded

**Pilot Height:**

0.375 inches

**Keyway Length:**

0.625 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Distance From End To Keyway Center:**

0.812 inches

**Thread Diameter:**

0.625 inches

**Ground Polarity Type:**

Negative

**Maximum Output Current Rating In Amps:**

55.0

**Rectifier Location:**

Integral

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.250 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.250 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

0.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

180.0

**Bottom Mounting Hole Diameter:**

0.505 inches

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.312 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

18

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

18

**Voltage In Volts:**

12.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700