

View Online at <https://aerobasegroup.com/nsn/2920-00-033-6564>

Thread Direction:

Right-hand

Thread Length:

0.688 inches

Furnished Items:

Cooling fan and oil deflector and voltage regulator and woodruff key

Second Step Diameter:

Between 0.7495 inches and 0.750 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.188 inches

Mounting Style:

Pilot mtd w/two mtg holes

Countersunk Mounting Hole Angle In Deg:

30.0

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

1.250 inches

Thread Diameter:

0.500 inches

Ground Polarity Type:

Positive

Maximum Output Current Rating In Amps:

25.0

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

360.0

Mounting Hole Largest Diameter:

0.500 inches

Mounting Pilot Outside Diameter:

Between 3.247 inches and 3.249 inches

Distance From Mounting Hole Center To End Of Housing:

1.750 inches

Mounting Pilot Depth:

3.000 inches

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

6.0

Special Features:

Vone pilot mtg hole

Fsc Application Data:

Engine electrical system, nonaircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700