

View Online at <https://aerobasegroup.com/nsn/2920-00-034-8722>

Mounting Slot Width:

0.281 inches

Mounting Slot Length:

0.344 inches

Submersibility:

Nonsubmersible

Mounting Facility Spacing:

1.747 in. Min 1.753 in. Maximum c to c

Voltage Rating:

12.0 volts

Closing Voltage Rating:

Between 7.0 volts and 9.0 volts

Opening Voltage Rating:

Between 3.0 volts and 5.0 volts

Pull-in Current:

Between 16.700 amperes and 19.500 amperes

Hold-in Current:

Between 2.1 amperes and 2.5 amperes

Plunger Stroke Length:

0.500 inches

Engaging Linkage:

Included

Linkage Adjustability:

Adjustable

Linkage Shift Lever Connection Type:

Threaded rod

Contact Manual Closing Provision:

Not included

Control Terminal Quantity:

2

Control Terminal Type:

Screw

Grounded Control Terminal:

Included

Main Terminal Quantity:

2

Main Terminal Type:

Stud

Motor Diameter For Which Rigid Mount Is Designed:

4.438 inches

Mounting Facility Type And Quantity:

4 slot

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T130-h