

View Online at <https://aerobasegroup.com/nsn/2920-00-034-8722>

**Mounting Slot Width:**

0.281 inches

**Mounting Slot Length:**

0.344 inches

**Submersibility:**

Nonsubmersible

**Mounting Facility Spacing:**

1.747 in. Min 1.753 in. Maximum c to c

**Voltage Rating:**

12.0 volts

**Closing Voltage Rating:**

Between 7.0 volts and 9.0 volts

**Opening Voltage Rating:**

Between 3.0 volts and 5.0 volts

**Pull-in Current:**

Between 16.700 amperes and 19.500 amperes

**Hold-in Current:**

Between 2.1 amperes and 2.5 amperes

**Plunger Stroke Length:**

0.500 inches

**Engaging Linkage:**

Included

**Linkage Adjustability:**

Adjustable

**Linkage Shift Lever Connection Type:**

Threaded rod

**Contact Manual Closing Provision:**

Not included

**Control Terminal Quantity:**

2

**Control Terminal Type:**

Screw

**Grounded Control Terminal:**

Included

**Main Terminal Quantity:**

2

**Main Terminal Type:**

Stud

**Motor Diameter For Which Rigid Mount Is Designed:**

4.438 inches

**Mounting Facility Type And Quantity:**

4 slot

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T130-h