## NSN 2920-00-056-8467

Engine Accessory Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-056-8467 **Thread Direction:** Right-hand Thread Length: 0.500 inches **Furnished Items:** Cooling fan and lockwasher and nut and woodruff key **Second Step Diameter:** 0.669 inches **Keyway Width:** 0.125 inches **Unthreaded Portion Length:** 0.750 inches **Mounting Hole Thread Direction:** Right-hand **Mounting Style:** Bracket mtd w/three mtg holes, top hole threaded **Environmental Protection:** Corrosion resistant **Keyway Length:** 0.625 inches Submersibility: Nonsubmersible **Shaft Rotation Direction:** Counterclockwise **Distance From End To Keyway Center:** 0.750 inches **Thread Diameter:** 0.669 inches **Ground Polarity Type:** Negative **Shaft Drive End Style:** Straight shaft end, threaded, w/keyway Distance Between Shaft Center And Bottom Mounting Hole Center: 3.750 inches **Distance Between Shaft Center And Top Mounting Hole Center:** 3.750 inches Angular Deviation Of First Hole From Top Center In Deg: 0.0 Angular Deviation Of Second Hole From First Hole In Deg:

180.0

**Distance Between Inside Surfaces Of Hinge Bracket:** 

Between 7.080 inches and 7.160 inches

## NSN 2920-00-056-8467

Engine Accessory Generator - Page 2 of 2



Distance Between Outside Surfaces Of Hinge Bracket:
Between 8.660 inches and 8.740 inches
<b>Bottom Mounting Hole Diameter:</b>
Between 0.379 inches and 0.387 inches
Thread Series:
Uns
Thread Class:
2a
Mounting Hole Thread Series Designator:
Unc
Mounting Hole Thread Diameter:
0.375 inches
Mounting Hole Thready Qty Per Inch (tpi):
16
Mounting Hole Thread Class:
2b
Thready Qty Per Inch (tpi):
20
Voltage In Volts:
24.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A14700