

View Online at <https://aerobasegroup.com/nsn/2920-00-074-3616>

Mounting Slot Width:

0.280 inches

Mounting Slot Length:

0.380 inches

Submersibility:

Nonsubmersible

Mounting Facility Spacing:

1.750 in. C to c

Voltage Rating:

12.0 volts

Closing Voltage Rating:

Between 2.6 volts and 6.6 volts

Opening Voltage Rating:

Between 0.6 volts and 2.1 volts

Pull-in Current:

Between 52.6 amperes and 59.0 amperes

Hold-in Current:

Between 12.7 amperes and 14.3 amperes

Plunger Stroke Length:

0.812 inches

Engaging Linkage:

Not included

Accommodated Linkage Threaded Hole Thread Size:

1/2-13

Contact Manual Closing Provision:

Not included

Control Terminal Quantity:

2

Control Terminal Type:

Screw

Grounded Control Terminal:

Included

Main Terminal Quantity:

2

Main Terminal Type:

Stud

Control Terminal Quantity Internally Connected To Main Terminal:

1

Motor Diameter For Which Rigid Mount Is Designed:

5.560 inches

Mounting Facility Type And Quantity:

4 slot

Surface Treatment:

Cadmium

Surface Treatment:

Cadmium plated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T130-h