

View Online at <https://aerobasegroup.com/nsn/2920-00-077-1440>

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Ground Polarity Type:

Positive

Maximum Output Current Rating In Amps:

5000.0

Minimum Current Cut-in Speed In Rpm:

1050

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.060 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.060 inches

Angular Deviation Of First Hole From Top Center In Deg:

17.0

Angular Deviation Of Second Hole From First Hole In Deg:

163.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 6.118 inches and 6.131 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 6.938 inches and 6.951 inches

Bottom Mounting Hole Diameter:

Between 0.323 inches and 0.333 inches

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.313 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700