

View Online at <https://aerobasegroup.com/nsn/2920-00-127-4680>

Thread Direction:

Right-hand

Thread Length:

0.790 inches

Furnished Items:

Lockwasher and nut and woodruff key

Second Step Diameter:

0.874 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.320 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Distance From End To Keyway Center:

2.110 inches

Thread Diameter:

0.625 inches

Ground Polarity Type:

Negative

Rectifier Location:

Integral

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.750 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.750 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 7.180 inches and 7.260 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 8.480 inches and 8.560 inches

Bottom Mounting Hole Diameter:

Between 0.451 inches and 0.463 inches

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700