

View Online at <https://aerobasegroup.com/nsn/2920-00-132-4695>

**Thread Direction:**

Right-hand

**Thread Length:**

0.460 inches

**Furnished Items:**

Lockwasher and nut and voltage regulator

**Second Step Diameter:**

Between 0.668 inches and 0.669 inches

**Keyway Width:**

0.125 inches

**Unthreaded Portion Length:**

0.840 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Keyway Length:**

0.625 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Clockwise

**Distance From End To Keyway Center:**

0.875 inches

**Thread Diameter:**

0.625 inches

**Input Current Rating:**

1.5 amperes

**Maximum Output Current Rating In Amps:**

18.0

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.062 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.062 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

196.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

164.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

7.127 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

7.917 inches

**Bottom Mounting Hole Diameter:**

0.320 inches

**Thread Series:**

Un

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.312 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

18

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

12.0

**Special Features:**

Supports grumman a10 aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700