

View Online at <https://aerobasegroup.com/nsn/2920-00-134-4652>

**Thread Direction:**

Right-hand

**Thread Length:**

0.113 inches

**Second Step Diameter:**

Between 0.668 inches and 0.669 inches

**Keyway Width:**

Between 0.126 inches and 0.128 inches

**Unthreaded Portion Length:**

1.310 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Keyway Length:**

Between 1.305 inches and 1.325 inches

**Submersibility:**

Submersible

**Shaft Rotation Direction:**

Clockwise or counterclockwise

**Distance From End To Keyway Center:**

1.349 inches

**Thread Diameter:**

0.625 inches

**Ground Polarity Type:**

Negative

**Armature Minimum Speed In Rpm At Full Current Output:**

2500

**Maximum Output Current Rating In Amps:**

60.0

**Minimum Current Cut-in Speed In Rpm:**

600

**Rectifier Location:**

Integral

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

Between 4.182 inches and 4.192 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

Between 4.182 inches and 4.192 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

160.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

200.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 7.243 inches and 7.256 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

Between 8.123 inches and 8.136 inches

**Bottom Mounting Hole Diameter:**

Between 0.448 inches and 0.458 inches

**Maximum Rated Armature Speed In Rpm:**

10000

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

18

**Voltage In Volts:**

28.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700