

View Online at <https://aerobasegroup.com/nsn/2920-00-136-8487>

Furnished Items:

Drive pulley

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Maximum Output Current Rating In Amps:

25.0

Rectifier Location:

Separate

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.062 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.062 inches

Angular Deviation Of First Hole From Top Center In Deg:

196.0

Angular Deviation Of Second Hole From First Hole In Deg:

164.0

Distance Between Inside Surfaces Of Hinge Bracket:

6.127 inches

Distance Between Outside Surfaces Of Hinge Bracket:

6.947 inches

Bottom Mounting Hole Diameter:

0.320 inches

Maximum Rated Armature Speed In Rpm:

2710

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thread Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

2b

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700