

View Online at <https://aerobasegroup.com/nsn/2920-00-215-4602>

**Thread Direction:**

Right-hand

**Thread Length:**

0.720 inches

**Furnished Items:**

Nut and woodruff key

**Second Step Diameter:**

0.669 inches

**Keyway Width:**

0.125 inches

**Unthreaded Portion Length:**

1.310 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Keyway Length:**

0.625 inches

**Submersibility:**

Nonsubmersible

**Shaft Rotation Direction:**

Counterclockwise

**Distance From End To Keyway Center:**

1.375 inches

**Thread Diameter:**

0.500 inches

**Rectifier Location:**

Separate

**Grounding Method:**

Internal

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.875 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.880 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

180.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

159.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 7.243 inches and 7.257 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

Between 8.123 inches and 8.137 inches

**Bottom Mounting Hole Diameter:**

Between 0.451 inches and 0.461 inches

**Thread Series:**

Unc

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

24.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700