

View Online at <https://aerobasegroup.com/nsn/2920-00-224-6200>

Thread Direction:

Right-hand

Thread Length:

0.438 inches

Furnished Items:

Drive pulley and voltage regulator

Second Step Diameter:

0.669 inches

Keyway Width:

0.125 inches

Unthreaded Portion Length:

0.812 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Keyway Length:

0.625 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

0.844 inches

Thread Diameter:

0.669 inches

Ground Polarity Type:

Negative

Armature Minimum Speed In Rpm At Full Current Output:

2150

Maximum Output Current Rating In Amps:

5.0

Minimum Current Cut-in Speed In Rpm:

880

Grounding Method:

Internal

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.016 inches

Distance Between Shaft Center And Top Mounting Hole Center:

2.938 inches

Angular Deviation Of First Hole From Top Center In Deg:

193.0

Angular Deviation Of Second Hole From First Hole In Deg:

125.0

Distance Between Inside Surfaces Of Hinge Bracket:

6.438 inches

Distance Between Outside Surfaces Of Hinge Bracket:

7.188 inches

Bottom Mounting Hole Diameter:

0.328 inches

Maximum Rated Armature Speed In Rpm:

2500

Thread Series:

Uns

Thread Class:

1a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.312 inches

Mounting Hole Thready Qty Per Inch (tpi):

18

Mounting Hole Thread Class:

1b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

12.0

Special Features:

Externalblastcooling

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700