

View Online at <https://aerobasegroup.com/nsn/2920-00-231-7270>

Thread Direction:

Right-hand

Thread Length:

0.625 inches

Furnished Items:

Lockwasher and nut

Second Step Diameter:

0.874 inches

Unthreaded Portion Length:

Between 1.260 inches and 2.175 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise or counterclockwise

Thread Diameter:

0.625 inches

Ground Polarity Type:

Negative

Minimum Current Cut-in Speed In Rpm:

5000

Grounding Method:

External

Shaft Drive End Style:

Straight shaft end, threaded

Distance Between Shaft Center And Bottom Mounting Hole Center:

Between 3.890 inches and 3.910 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.900 inches

Angular Deviation Of First Hole From Top Center In Deg:

0.0

Angular Deviation Of Second Hole From First Hole In Deg:

180.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 3.940 inches and 4.010 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 5.060 inches and 5.130 inches

Bottom Mounting Hole Diameter:

Between 0.513 inches and 0.523 inches

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Uns

Mounting Hole Thread Diameter:

0.500 inches

Mounting Hole Thready Qty Per Inch (tpi):

12-1/2

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700