

View Online at <https://aerobasegroup.com/nsn/2920-00-231-7384>

**Thread Direction:**

Right-hand

**Thread Length:**

Any acceptable

**Furnished Items:**

Bolt and cooling fan and lockwasher and nut

**Second Step Diameter:**

Between 0.873 inches and 0.874 inches

**Unthreaded Portion Length:**

Any acceptable

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant

**Submersibility:**

Nonsubmersible

**Maximum Operating Altitude Rating:**

Not rated

**Shaft Rotation Direction:**

Clockwise or counterclockwise

**Thread Diameter:**

0.625 inches

**Ground Polarity Type:**

Negative

**Maximum Output Current Rating In Amps:**

75.0

**Rectifier Location:**

Separate

**Grounding Method:**

External

**Shaft Drive End Style:**

Straight shaft end, threaded

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.900 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.900 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

0.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

180.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

3.975 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

5.325 inches

**Bottom Mounting Hole Diameter:**

0.518 inches

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Uns

**Mounting Hole Thread Diameter:**

0.500 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

12-1/2

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

18

**Voltage In Volts:**

12.0

**Special Features:**

Hex hole in shaft end, 2.260 in. Depth, 0.315 across flats

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700