NSN 2920-00-235-1686

Electrical Engine Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-235-1686

| Mounting Hole D | iameter: |
|-------------------|--|
| Between 0.654 ind | ches and 0.664 inches |
| Mounting Hole C | ircle Radius: |
| 2.875 inches | |
| Mounting Flange | Shape Style: |
| Triangular | |
| Engaging Mecha | nism Style: |
| Peripheral outboa | rd gear drive w/worm shaft, shaft, shift lever, collar and over-running clutch w/drive housing |
| Engaging Mecha | nism Opening Angular Deviation In Deg: |
| 107.0 | |
| Lever Actuation | Method: |
| Solenoid | |
| Lock Test Currer | nt Rating In Amps: |
| 800.0 | |
| Shaft Rotation D | irection: |
| Clockwise | |
| Armature Actuat | ion Device Type: |
| Relay-solenoid | |
| Engaging Mecha | nism To Armature Positional Relationship: |
| Straight | |
| Mounting Flange | Angular Deviation In Deg: |
| 322.5 | |
| Voltage In Volts: | |
| 24.0 | |
| Terminal Type A | nd Quantity: |
| 1 threaded stud | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A23400 | |