

View Online at <https://aerobasegroup.com/nsn/2920-00-237-1711>

Mounting Slot Width:

0.281 inches

Mounting Slot Length:

0.344 inches

Submersibility:

Nonsubmersible

Mounting Facility Spacing:

1.750 in. C to c on mtg centers 66deg apart in 2.562 in. Radius

Voltage Rating:

12.0 volts

Closing Voltage Rating:

8.5 volts

Opening Voltage Rating:

Between 3.5 volts and 4.2 volts

Pull-in Current:

Between 49.0 amperes and 55.0 amperes

Hold-in Current:

Between 11.0 amperes and 13.0 amperes

Plunger Stroke Length:

0.750 inches

Engaging Linkage:

Not included

Accommodated Linkage Threaded Hole Thread Size:

1/2-20

Contact Manual Closing Provision:

Not included

Control Terminal Quantity:

1

Control Terminal Type:

Stud

Grounded Control Terminal:

Not included

Main Terminal Quantity:

2

Main Terminal Type:

Stud

Control Terminal Quantity Internally Connected To Main Terminal:

1

Motor Diameter For Which Rigid Mount Is Designed:

5.125 inches

Mounting Facility Type And Quantity:

4 slot

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T130-h