

View Online at <https://aerobasegroup.com/nsn/2920-00-237-1711>

**Mounting Slot Width:**

0.281 inches

**Mounting Slot Length:**

0.344 inches

**Submersibility:**

Nonsubmersible

**Mounting Facility Spacing:**

1.750 in. C to c on mtg centers 66deg apart in 2.562 in. Radius

**Voltage Rating:**

12.0 volts

**Closing Voltage Rating:**

8.5 volts

**Opening Voltage Rating:**

Between 3.5 volts and 4.2 volts

**Pull-in Current:**

Between 49.0 amperes and 55.0 amperes

**Hold-in Current:**

Between 11.0 amperes and 13.0 amperes

**Plunger Stroke Length:**

0.750 inches

**Engaging Linkage:**

Not included

**Accommodated Linkage Threaded Hole Thread Size:**

1/2-20

**Contact Manual Closing Provision:**

Not included

**Control Terminal Quantity:**

1

**Control Terminal Type:**

Stud

**Grounded Control Terminal:**

Not included

**Main Terminal Quantity:**

2

**Main Terminal Type:**

Stud

**Control Terminal Quantity Internally Connected To Main Terminal:**

1

**Motor Diameter For Which Rigid Mount Is Designed:**

5.125 inches

**Mounting Facility Type And Quantity:**

4 slot

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T130-h