## NSN 2920-00-246-3301



Engine Accessory Generator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/2920-00-246-3301 **Thread Direction:** Right-hand Thread Length: 0.375 inches **Pilot Diameter:** 2.000 inches **Second Step Diameter:** 0.625 inches **Keyway Width:** 0.125 inches **Unthreaded Portion Length:** 1.062 inches **Mounting Hole Thread Direction:** Right-hand **Mounting Style:** Flange mtd w/two mtg holes, top hole threaded **Pilot Height:** 0.312 inches **Keyway Length:** 0.500 inches Submersibility: Nonsubmersible **Shaft Rotation Direction:** Clockwise **Distance From End To Keyway Center:** 0.812 inches **Thread Diameter:** 0.625 inches **Ground Polarity Type:** Negative **Shaft Drive End Style:** Straight shaft end, threaded, w/keyway Distance Between Shaft Center And Bottom Mounting Hole Center: **3.187** inches **Distance Between Shaft Center And Top Mounting Hole Center:** 3.187 inches Angular Deviation Of First Hole From Top Center In Deg: 180.0

Angular Deviation Of Second Hole From First Hole In Deg: 180.0

**Bottom Mounting Hole Diameter:** 

0.437 inches

## NSN 2920-00-246-3301

Engine Accessory Generator - Page 2 of 2



Thread Series:
Unf
Thread Class:
2a
Mounting Hole Thread Series Designator:
Unc
Mounting Hole Thread Diameter:
0.312 inches
Mounting Hole Thready Qty Per Inch (tpi):
18
Mounting Hole Thread Class:
2b
Thready Qty Per Inch (tpi):
18
Voltage In Volts:
12.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A14700