Electrical Engine Starter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-268-2971

| Manufine Hala Diama    |   |
|------------------------|---|
| Mounting Hole Diame    |   |
| 0.414 mils and 0.434   |   |
| Mounting Hole Circle   | Radius:   |
| 2.500 inches           |   |
| Mounting Flange Sha    | pe Style:   |
| Triangular             |   |
| Engaging Mechanism     | -   |
| -                      | ar drive w/worm shaft, shaft, shift lever, collar and over-running clutch w/drive housing |
|                        | Opening Angular Deviation In Deg:   |
| 225.0                  |   |
| Lever Actuation Meth   | od:   |
| Solenoid               |   |
| Shaft Rotation Directi | on:   |
| Clockwise              |   |
| Armature Actuation D   | Device Type:  |
| Relay-solenoid         |   |
| Engaging Mechanism     | To Armature Positional Relationship:  |
| Straight               |   |
| Mounting Flange Ang    | ular Deviation In Deg:  |
| 45.0                   |   |
| Voltage In Volts:      |   |
| 12.0                   |   |
| Terminal Type And Q    | uantity:  |
| 3 threaded stud        |   |
| Shelf Life:            |   |
| N/a                    |   |
| Unit Of Measure:       |   |
|                        |   |
| Demilitarization:      |   |
| No                     |   |
| Fiig:                  |   |
| A23400                 |   |