NSN 2920-00-269-7110

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-269-7110 **Mounting Slot Width:** 0.281 inches **Mounting Slot Length:** 0.344 inches Submersibility: Nonsubmersible **Mounting Facility Spacing:** 1.750 in. C to c 60 degrees apart on 2.781 in. Radius Voltage Rating: 32.0 volts **Hold-in Current:** Between 5.1 amperes and 5.7 amperes **Plunger Stroke Length:** 0.750 inches **Engaging Linkage:** Not included Accommodated Linkage Threaded Hole Thread Size: 1/2-20 **Contact Manual Closing Provision:** Not included **Control Terminal Quantity:** 2 **Control Terminal Type:** Stud **Grounded Control Terminal:** Included **Main Terminal Quantity: Main Terminal Type:** Stud **Control Terminal Quantity Internally Connected To Main Terminal:** Motor Diameter For Which Rigid Mount Is Designed: 5.562 inches **Mounting Facility Type And Quantity:** 4 slot Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 2920-00-269-7110

Electrical Engine Starter Relay-solenoid - Page 2 of 2



Fiig:

T130-h