NSN 2920-00-269-7111

Electrical Engine Starter Relay-solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2920-00-269-7111 **Mounting Slot Width:** 0.281 inches **Mounting Slot Length:** 0.344 inches Submersibility: Nonsubmersible **Mounting Facility Spacing:** 1.750 in. C to c 66 degrees apart on 2.562 in. Radius Voltage Rating: 24.0 volts **Pull-in Current:** Between 34.700 amperes and 38.200 amperes **Hold-in Current:** Between 6.0 amperes and 6.9 amperes **Engaging Linkage:** Not included Accommodated Linkage Threaded Hole Thread Size: 1/2-20 **Contact Manual Closing Provision:** Not included **Control Terminal Quantity:** 2 **Control Terminal Type:** Stud **Grounded Control Terminal:** Included **Main Terminal Quantity: Main Terminal Type:** Motor Diameter For Which Rigid Mount Is Designed: 5.125 inches **Mounting Facility Type And Quantity:** 4 slot **Special Features:** Fungus and corrosion resistant Shelf Life: **Unit Of Measure:**

N/a
Unit Of Measure:
-Demilitarization:

NSN 2920-00-269-7111

Electrical Engine Starter Relay-solenoid - Page 2 of 2



Fiig:

T130-h