

View Online at <https://aerobasegroup.com/nsn/2920-00-293-4380>

**Thread Direction:**

Right-hand

**Thread Length:**

0.796 inches

**Second Step Diameter:**

Between 0.668 inches and 0.669 inches

**Keyway Width:**

0.125 inches

**Unthreaded Portion Length:**

1.235 inches

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant and fungus resistant

**Keyway Length:**

0.625 inches

**Submersibility:**

Submersible

**Shaft Rotation Direction:**

Counterclockwise

**Distance From End To Keyway Center:**

1.391 inches

**Thread Diameter:**

0.500 inches

**Armature Minimum Speed In Rpm At Full Current Output:**

1600

**Maximum Output Current Rating In Amps:**

25.0

**Minimum Current Cut-in Speed In Rpm:**

1250

**Grounding Method:**

Internal

**Shaft Drive End Style:**

Straight shaft end, threaded, w/keyway

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

Between 3.874 inches and 3.876 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

Between 3.874 inches and 3.876 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

159.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

201.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 7.243 inches and 7.257 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

Between 8.118 inches and 8.132 inches

**Bottom Mounting Hole Diameter:**

Between 0.432 inches and 0.442 inches

**Maximum Rated Armature Speed In Rpm:**

8000

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.375 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

16

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

20

**Voltage In Volts:**

24.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A14700