## NSN 2920-00-293-5247

Spark Plug - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2920-00-293-5247

view Offilite at https://aerobasegroup.com/histi/2920-00-293-3247
Body Style:
Electrically shielded, full insulator, gasket seat
Dc Resistance Rating In Ohms:
Between 10000.0 and 20000.0
Reach Length:
0.375 inches
Usage Design:
Engine other than aircraft
Width Across Flats:
0.812 inches
Electrode Style:
Single flat shell ground electrode (see also style 4)
Thread Size And Series/type Designator And Location:
14-1.25mm base err-100
Mean Effective Pressure Rating:
Between 115.0 pounds per square inch and 116.0 pounds per square inch
Seat Major Diameter:
0.938 inches
Height Above Mounting Surface:
3.250 inches
Top To Terminal Contact Distance:
Between 1.000 inches and 1.050 inches
Top To Shield Thread Distance:
0.125 inches
Shield Thread Length:
0.438 inches
Terminal Sleeve Inside Diameter:
Between 0.378 inches and 0.387 inches
Test Data Document:
81348-ws506 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
2 type and a class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A10400