

View Online at <https://aerobasegroup.com/nsn/2920-00-294-3479>

Thread Direction:

Right-hand

Thread Length:

0.906 inches

Spline Minor Diameter:

Any acceptable

Spline Major Diameter:

0.874 inches

Spline Width:

Between 0.216 inches and 0.217 inches

Spline Quantity:

6

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Bracket mtd w/three mtg holes, top hole threaded

Environmental Protection:

Corrosion resistant

Submersibility:

Nonsubmersible

Maximum Operating Altitude Rating:

Not rated

Shaft Rotation Direction:

Clockwise

Thread Diameter:

0.625 inches

Spline Length:

1.938 inches

Armature Minimum Speed In Rpm At Full Current Output:

1500

Maximum Output Current Rating In Amps:

26.0

Minimum Current Cut-in Speed In Rpm:

880

Grounding Method:

Internal

Shaft Drive End Style:

Splined shaft end, threaded

Cotter Pin Hole:

Included

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.875 inches

Distance Between Shaft Center And Top Mounting Hole Center:

3.500 inches

Angular Deviation Of First Hole From Top Center In Deg:

8.0

Angular Deviation Of Second Hole From First Hole In Deg:

201.0

Distance Between Inside Surfaces Of Hinge Bracket:

Between 7.243 inches and 7.257 inches

Distance Between Outside Surfaces Of Hinge Bracket:

Between 8.181 inches and 8.195 inches

Bottom Mounting Hole Diameter:

Between 0.328 inches and 0.453 inches

Maximum Rated Armature Speed In Rpm:

1800

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.438 inches

Mounting Hole Thready Qty Per Inch (tpi):

14

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

12.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700