

View Online at <https://aerobasegroup.com/nsn/2920-00-294-3479>

**Thread Direction:**

Right-hand

**Thread Length:**

0.906 inches

**Spline Minor Diameter:**

Any acceptable

**Spline Major Diameter:**

0.874 inches

**Spline Width:**

Between 0.216 inches and 0.217 inches

**Spline Quantity:**

6

**Mounting Hole Thread Direction:**

Right-hand

**Mounting Style:**

Bracket mtd w/three mtg holes, top hole threaded

**Environmental Protection:**

Corrosion resistant

**Submersibility:**

Nonsubmersible

**Maximum Operating Altitude Rating:**

Not rated

**Shaft Rotation Direction:**

Clockwise

**Thread Diameter:**

0.625 inches

**Spline Length:**

1.938 inches

**Armature Minimum Speed In Rpm At Full Current Output:**

1500

**Maximum Output Current Rating In Amps:**

26.0

**Minimum Current Cut-in Speed In Rpm:**

880

**Grounding Method:**

Internal

**Shaft Drive End Style:**

Splined shaft end, threaded

**Cotter Pin Hole:**

Included

**Distance Between Shaft Center And Bottom Mounting Hole Center:**

3.875 inches

**Distance Between Shaft Center And Top Mounting Hole Center:**

3.500 inches

**Angular Deviation Of First Hole From Top Center In Deg:**

8.0

**Angular Deviation Of Second Hole From First Hole In Deg:**

201.0

**Distance Between Inside Surfaces Of Hinge Bracket:**

Between 7.243 inches and 7.257 inches

**Distance Between Outside Surfaces Of Hinge Bracket:**

Between 8.181 inches and 8.195 inches

**Bottom Mounting Hole Diameter:**

Between 0.328 inches and 0.453 inches

**Maximum Rated Armature Speed In Rpm:**

1800

**Thread Series:**

Unf

**Thread Class:**

2a

**Mounting Hole Thread Series Designator:**

Unc

**Mounting Hole Thread Diameter:**

0.438 inches

**Mounting Hole Thready Qty Per Inch (tpi):**

14

**Mounting Hole Thread Class:**

2b

**Thready Qty Per Inch (tpi):**

18

**Voltage In Volts:**

12.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A14700