

View Online at <https://aerobasegroup.com/nsn/2920-00-294-3558>

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Second Step Diameter:

0.750 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

0.750 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Body mtd w/four threaded mtg holes

Pilot Height:

0.250 inches

Environmental Protection:

Corrosion resistant

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Counterclockwise

Distance From End To Keyway Center:

0.875 inches

Thread Diameter:

0.500 inches

Ground Polarity Type:

Negative or positive

Armature Minimum Speed In Rpm At Full Current Output:

2000

Maximum Output Current Rating In Amps:

10.0

Minimum Current Cut-in Speed In Rpm:

1200

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance From Raised Face To First Mounting Hole Center:

2.750 inches

Angular Deviation Of First Hole From Top Center In Deg:

125.0

Angular Deviation Of Second Hole From First Hole In Deg:

90.0

Distance From Raised Face To Second Mounting Center:

6.750 inches

Maximum Rated Armature Speed In Rpm:

3000

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unf

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

24

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

20

Voltage In Volts:

24.0

Special Features:

Shaft drilled for cotter pin 3 threaded post type terminals, 2 ea 1/4-20 thd, 1 ea 10-24 thd

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700