

View Online at <https://aerobasegroup.com/nsn/2920-00-294-3815>

**Body Material:**

Iron, cast

**Drive Connection Type:**

Rigid coupled

**Shaft Length:**

1.020 inches

**Drive Shaft Type:**

Plain

**Shaft Rotation Direction:**

Clockwise

**Distributor Cap:**

Included

**Mounting Method:**

Clamp

**Impulse Quantity Per Revolution:**

6

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Push-in

**Coil Terminal Type:**

Push-in

**Primary Terminal Accommodation Type:**

Stud

**Spark Advance Control Method:**

Centrifugal

**Maximum Advance Deg:**

16.0

**Contact Set Quantity:**

1

**Rpm At Maximum Advance:**

1600.0

**Primary Terminal Accommodation Thread Series:**

Unc

**Spark Distribution Method:**

Contact

**Primary Terminal Accommodation Thread Diameter:**

0.164 inches

**Primary Terminal Accommodation Thread Qty Per Inch (tpi):**

32

**Special Features:**

Surface treatment black enamel

**Surface Treatment:**

Enamel

**Surface Treatment:**

Enamel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A12200