

View Online at <https://aerobasegroup.com/nsn/2920-00-294-3819>

**Body Material:**

Aluminum alloy

**Drive Connection Type:**

Impulse coupled

**Distance Between Mounting Facility Centers:**

1.968 inches

**Performance Type:**

High tension

**Shaft Rotation Direction:**

Clockwise

**Mounting Facility Quantity:**

4

**Pole Quantity:**

2

**Distributor Cap:**

Included

**Mounting Method:**

Base

**Impulse Quantity Per Revolution:**

4

**Ignition Type For Which Designed:**

Single

**Secondary Terminal Type:**

Threaded

**Spark Plug Terminal Accommodation Thread Series:**

Unef

**Rotation Element Type:**

Permanent magnet rotor

**Contact Set Quantity:**

1

**Mounting Facility:**

Threaded hole

**Features Provided:**

Radio interference shielding

**Spark Distribution Method:**

Gap

**Spark Plug Terminal Accommodation Thread Diameter:**

0.688 inches

**Spark Plug Terminal Accommodation Thread Qty Per Inch (tpi):**

24

**Mounting Facility Thread Series:**

Unc

**Mounting Facility Thread Diameter:**

0.375 inches

**Mounting Facility Thready Qty Per Inch (tpi):**

16

**Surface Treatment:**

Any acceptable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A12200