

View Online at <https://aerobasegroup.com/nsn/2920-00-294-3913>

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Furnished Items:

Cooling fan and woodruff key

Second Step Diameter:

0.874 inches

Keyway Width:

0.156 inches

Unthreaded Portion Length:

1.312 inches

Mounting Hole Thread Direction:

Right-hand

Mounting Style:

Base flanged mtd w/ four threaded mtg holes

Center To Center Distance Between Mounting Holes Along Width:

2.250 inches

Center To Center Distance Between Mounting Holes Along Length:

2.500 inches

Environmental Protection:

Corrosion resistant and fungus resistant

Keyway Length:

0.750 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

1.109 inches

Thread Diameter:

0.625 inches

Armature Minimum Speed In Rpm At Full Current Output:

1125

Maximum Output Current Rating In Amps:

10.0

Minimum Current Cut-in Speed In Rpm:

975

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance From Raised Face To First Mounting Hole Center:

2.250 inches

Distance From Shaft Centerline To Mounting Flange Surface:

3.125 inches

Maximum Rated Armature Speed In Rpm:

3000

Thread Series:

Unf

Thread Class:

2a

Mounting Hole Thread Series Designator:

Unc

Mounting Hole Thread Diameter:

0.375 inches

Mounting Hole Thready Qty Per Inch (tpi):

16

Mounting Hole Thread Class:

2b

Thready Qty Per Inch (tpi):

18

Voltage In Volts:

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A14700