

View Online at <https://aerobasegroup.com/nsn/2920-00-294-3917>

Thread Direction:

Right-hand

Thread Length:

0.781 inches

Pilot Diameter:

3.249 inches

Furnished Items:

Overload protective device

Second Step Diameter:

0.999 inches

Keyway Width:

0.250 inches

Unthreaded Portion Length:

1.188 inches

Mounting Style:

Flange mtd w/three mtg holes

Center To Center Distance Between Mounting Holes Along Width:

3.625 inches

Pilot Height:

1.000 inches

Environmental Protection:

Corrosion resistant

Keyway Length:

1.000 inches

Submersibility:

Nonsubmersible

Shaft Rotation Direction:

Clockwise

Distance From End To Keyway Center:

1.312 inches

Thread Diameter:

0.875 inches

Armature Minimum Speed In Rpm At Full Current Output:

2000

Maximum Output Current Rating In Amps:

15.0

Minimum Current Cut-in Speed In Rpm:

1000

Shaft Drive End Style:

Straight shaft end, threaded, w/keyway

Distance Between Shaft Center And Bottom Mounting Hole Center:

3.062 inches

Top Mounting Hole Diameter:

0.562 inches

Bottom Mounting Hole Diameter:

0.469 inches

Center To Center Distance Between Top Mounting Slot And Bottom Mounting Hole:

5.875 inches

Maximum Rated Armature Speed In Rpm:

3500

Thread Series:

Unf

Thread Class:

2a

Thready Qty Per Inch (tpi):

14

Voltage In Volts:

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A14700